



TRON

L U B R I C A N T S

 **ULTRON**

 **MEGATRON**

 **POWERTRON**

Technical Data Sheet

Megatron Concentrate Antifreeze / Coolant 80%

Application

Megatron Concentrate Antifreeze/ Coolant is recommended in all water cooled internal combustion engines to protect against corrosion and frost damage. This Product is a concentrated solution that **MUST be diluted with water in a ratio of 1:1 prior to use**. The Low Silicate additive technology ensures efficient and long lasting protection of the engine and cooling system for up to 2 years. Recommended final fluid concentration is between 33% and 50 % by volume.

Table Dilutions

Number of Parts Concentrate Antifreeze	1	1	1
Number of Parts Water	1	1.5	2
Freezing Protection ,C	-38	-25	-18

Description

A superior quality, ethylene glycol based, antifreeze and cooling system conditioner that is specially developed to allow the end user a choice of dilution ratios. Megatron Concentrate Antifreeze/Coolant is miscible with water of any proportion and is compatible with hard or tap water, however distilled water is recommended for dilution.

Benefits

- Excellent pitting protection for wet sleeve cylinder liners.
- Reduced hard water scale.
- Improved water pump seal life due to low dissolved solids level.
- Remarkable heat transfer capabilities.

Typical Physical Characteristics

Megatron Concentrate Antifreeze/Coolant	
Density @ 20°C	1.070
Colour	Fluorescent Yellow
Freezing Point min.(50% v/v) °C	-38
Boiling Point min.(50% v/v) °C	110
Water Content %	14
pH	8.25

The values of the specifications shown in this table are typical values given as an indication only.

Pack Sizes

- 500 ml ,1 Litre, 5 Litre and 20 Litre Plastic Bottles
- 208 Litre Steel Drums
- 1000 Litre IBC

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data sheet available on www.tronlubricants.com

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.