



**TRON**  
L U B R I C A N T S

 **ULTRON**

 **MEGATRON**

 **POWERTRON**

## Technical Data Sheet

### Megatron Automatic Transmission Fluid Dexron II D

#### Specifications, Performance Standards & Recommendations

- DEXRON II D
- ALLISON C-4
- CATERPILLAR TO-2
- Power Steering

Megatron ATF DX II D is recommended for many passenger car, heavy duty automatic transmissions power steering and finds application in a wide variety of industrial hydraulic pumps and motors.

#### Description

Megatron high quality automatic transmission fluid is made from solvent refined base oils, antioxidants, anti-wear agents, detergents and defoamant that provides consistent, reliable, smooth and trouble free operations of many automotive transmission systems.

#### Key Advantages

- High oxidation resistance ensures consistent performance.
- Dependable anti-wear protection ensures longer component life that is required for reliable gear and hydraulic pump application.
- Correct frictional characteristics giving smooth transmission and perfect synchronisation.

#### Typical Physical Characteristics

Megatron ATF	DX-II D
Viscosity, cSt @ 40°C	41.0
Viscosity, cSt @ 100°C	7.5
Viscosity Index	120
Pour Point, °C	-23
Flash Point, °C	220
Colour, Visual	RED

The values of the specifications shown in this table are typical values given as an indication only.

#### Pack Sizes

- 500 ml ,1 Litre, 5 Litre and 20 Litre Plastic Bottles
- 208 Litre Steel Drums
- 1000 Litre IBC

#### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data sheet available on [www.tronlubricants.com](http://www.tronlubricants.com)

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.