



# TRON

L U B R I C A N T S

 **ULTRON**

 **MEGATRON**

 **POWERTRON**

## Technical Data Sheet

### Megatron Monograde Automotive Engine Lubricant Range

#### Specification, Performance Standards & Recommendations

- API SF/CF

Megatron Monograde Automotive Engine Lubricant Range is recommended for older petrol and naturally aspirated diesel engines of passenger cars, light commercial vehicles and farm equipment, for which single viscosity grades are specified. They are also used as running-in and flushing oils for recently overhauled engines. The SAE 50 grade is used for gearboxes where Extreme Pressure Oils are not suitable. Always consult the manufacturers operating manual as to the suitability of the lubricant.

#### Description

Megatron range of monograde motor oils is intended for passenger cars, light trucks and bakkies as well as certain farm equipment, where conventional single grade oils are preferred. These oils have good lubricating properties and will provide satisfactory protection against wear and oxidation and prolong engine life.

#### Benefits

- Provides excellent lubrication.
- Keeps engines clean.
- Prolongs engine life.
- Cost effective.

#### Typical Physical Characteristics

Megatron Monograde				
SAE No.	10W	30	40	50
Viscosity, cSt @ 40°C	37.5	95	124	232
Viscosity, cSt @ 100°C	6.2	10.9	14.8	20.1
Viscosity Index	112	104	100	99
Flash Point, °C	214	232	238	242
Pour Point, °C	-33	-21	-21	-18
Total Base No., mg KOH/g	6	6	6	6

The values of the specifications shown in this table are typical values given as an indication only.

#### Pack Sizes

- 500 ml ,1 Litre, 5 Litre and 20 Litre Plastic Bottles
- 208 Litre Steel Drums
- 1000 Litre IBC

#### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data sheet available on [www.tronlubricants.com](http://www.tronlubricants.com)

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.