



TRON

L U B R I C A N T S

 **ULTRON**

 **MEGATRON**

 **POWERTRON**

Technical Data Sheet

Megatron EP 90 GL-4

Specifications, Approvals & recommendations

- API GL-4
- US STEEL224
- 51517 Part III
- ZF-TE-ML
- MT-1

Megatron EP 90 GL- 4 is recommended for manual transmission of passenger cars, commercial vehicles and construction equipment. It is suitable for transmission/axle combinations, synchromesh gearboxes and other applications which require a relatively low level of EP additives.

Description

This monograde product contains Extreme Pressure additives comprising of Sulphur – Phosphorous technology that is specially recommended for synchromesh transmissions proven to provide full protection to bronze components, ensuring reliable operation and smooth gear changes.

Benefits

- Good anti-wear and load carrying characteristics that extends the life of components.
- Improved protection against rust and corrosion.
- Reduces synchromesh cone slippage and overheating.
- Ensures increased component life.

Typical Physical Characteristics

Megatron GL-4	
SAE No.	90
Viscosity, cSt @ 40°C	140
Viscosity, cSt @ 100°C	16.3
Viscosity Index	95
Flash Point, °C	236
Pour Point, °C	--18

The values of the specifications shown in this table are typical values given as an indication only.

Pack Sizes

- 500 ml , 1 Litre, 5 Litre and 20 Litre Plastic Bottles
- 208 Litre Steel Drums
- 1000 Litre IBC

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data sheet available on www.tronlubricants.com

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.