



# TRON

L U B R I C A N T S

 **ULTRON**

 **MEGATRON**

 **POWERTRON**

## Technical Data Sheet

### Megatron EP 90 GL-5

#### Specification, Approvals & Recommendations

- API GL-5
- US STEEL224
- 51517 PART III
- MT1
- ZF-TE-ML-05A
- SCANIA STO 1:0
- MACK GO-J plus
- SAE J2360

Megatron EP 90 GL-5 is recommended for automotive gear boxes, differentials and hypoid gear sets in motorcycles, passenger cars, commercial vehicles, off-road construction and agricultural equipment where an API Service Designation GL-5 is required. It may also be used for Ancillary equipment gear sets and some industrial equipment.

#### Description

Premium quality range containing sulphur-phosphorous EP additives developed to meet the rigorous demands of commercial fleet manual transmissions, drive axles and final drives. They are also suitable for similar components of farm and contactor equipment and passenger cars and when properly applied at the intervals recommended by car manufacturers,

#### Benefits

- Resistance to high temperature oxidation providing extended drain capability.
- Protection against wear and scoring under all operating conditions, high speed, high torque and shock loading.
- High load carrying capability ensures gears operating under high loads are protected thus prolonging component life.

#### Typical Physical Characteristics

Megatron GL- 5	
SAE No.	90
Viscosity, cSt @ 40 <sup>0</sup> C	180
Viscosity, cSt @ 100 <sup>0</sup> C	17
Viscosity Index, min	95
Flash Point, <sup>0</sup> C	236
Pour Point, <sup>0</sup> C	-21

The values of the specifications shown in this table are typical values given as an indication only.

#### Pack Sizes

- 500 ml ,1 Litre, 5 Litre and 20 Litre Plastic Bottles
- 208 Litre Steel Drums
- 1000 Litre IBC

#### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data sheet available on [www.tronlubricants.com](http://www.tronlubricants.com)

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.