



TRON

L U B R I C A N T S

 **ULTRON**

 **MEGATRON**

 **POWERTRON**

Technical Data Sheet

Megatron Slideway Range

Specifications, Approvals & Recommendations

Megatron slideway range is recommended for lubricating the slide ways of machine tools, planers, lathes and the slides and guides of other types of machines where a tacky, non-corrosive EP lubricant is required.

This machine tool lubricant also meets the requirements of hydraulic systems, gear boxes and spindles in most machine tools and is specially designed for table way lubrication, with emphasis on superior stick-slip properties.

Description

Megatron's Range of Slideway oils are specially designed for the lubrication of machine tools slides, feed mechanisms and tables. Blended using highly refined based stocks and special additives, to enhance the critical property of adhesion that reduces stick/slip.

Benefits

- Good slideway adhesion
- Excellent frictional properties
- Provides high levels of corrosion protection
- Anti-wear additives prevents the wear of critical sliding surfaces
- Can be used on all horizontal and vertical slide ways

Typical Physical Properties

Megatron Slideway			
SAE No.	32	68	220
Viscosity, cSt @ 40°C	32	68	220
Viscosity, cSt @ 100°C	5.6	8.6	18.7
Viscosity Index	100	100	100
Flash Point, °C	220	224	230
Pour Point, °C	-25	-25	-25

The values of the specifications shown in this table are typical values given as an indication only.

Pack Sizes

- 500 ml , 1 Litre, 5 Litre and 20 Litre Plastic Bottles
- 208 Litre Steel Drums
- 1000 Litre IBC

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data sheet available on www.tronlubricants.com

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.